

# SAFETY DATA SHEET



Revision date 03/20/2024

Revision Number 2

## 1. Identification

### Product identifier

**Product Name** Spray Lube "A"

### Other means of identification

**Safety data sheet number** 04951

**Product Code(s)** L0034-063, L0034-063C

**UN number or ID number** UN1950

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended use** No information available

**Restrictions on use** No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

Lubriplate Lubricants Company Headquarters  
129 Lockwood St.  
Newark, NJ 07105  
Midwest Office & Plant  
1500 Oakdale Ave.  
Toledo, OH 43605  
419-691-2491  
419-693-3806

### Emergency telephone number

**Emergency Telephone** Chem-Tel 1-800-255 3924 (US & Canada only)  
01-813-248-0585 (Outside US & Canada)

## 2. Hazard(s) identification

### Classification

Flammable gases	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

### Hazards not otherwise classified (HNOC)

Not applicable

**Label elements****Danger****Hazard statements**

Extremely flammable gas

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

**Appearance** Aerosol**Physical state** Aerosol**Odor** Mild**Precautionary Statements - Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

**Precautionary Statements - Response**

Eliminate all ignition sources if safe to do so

Leaking gas fire: Do not extinguish, unless leak can be stopped safely

**Precautionary Statements - Storage**

Store in a well-ventilated place

Protect from sunlight. Store in a well-ventilated place

Do not expose to temperatures exceeding 50 °C/122 °F

**Other information**

No information available.

**3. Composition/information on ingredients****Substance**

Not applicable.

**Mixture**

Chemical name	CAS No.	Weight-%	Trade secret
Distillates (petroleum), hydrotreated light	64742-47-8	30 - <60 %	*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	15 - <40%	*
propane	74-98-6	10 - <30%	*
isobutane	75-28-5	5 - <10%	*
Lithium stearate	4485-12-5	1 - <5%	*
Precipitated calcium carbonate	471-34-1	0.5 - <1.5%	*
zinc oxide	1314-13-2	0.1 - <1%	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First-aid measures

### Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
<b>Ingestion</b>	Rinse mouth.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	No information available.
-----------------	---------------------------

### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b> Large Fire	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	Yes.
<b>Sensitivity to static discharge</b>	Yes.
<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire
-----------------------------	--

and explosion hazard. Do not cut, puncture or weld containers.

**Other information** Ventilate the area.

### Methods and material for containment and cleaning up

**Methods for containment** Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

## 7. Handling and storage

### Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

## 8. Exposure controls/personal protection

### Control parameters

**Exposure Limits** The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter excluding metal working fluids, highly & severely refined	TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	IDLH: 2500 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
propane 74-98-6	Simple asphyxiant (See Appendix F: Minimal Oxygen Content) : See Appendix F: Minimal Oxygen Content, explosion	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> STEL: 1250 ppm STEL: 2250 mg/m <sup>3</sup>

	hazard		
isobutane 75-28-5	STEL: 1000 ppm explosion hazard	-	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
Lithium stearate 4485-12-5	TWA: 10 mg/m <sup>3</sup> inhalable particulate matter except stearates of toxic metals TWA: 3 mg/m <sup>3</sup> respirable particulate matter except stearates of toxic metals	-	-
Precipitated calcium carbonate 471-34-1	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
zinc oxide 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable particulate matter TWA: 2 mg/m <sup>3</sup> respirable particulate matter	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> fume (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) STEL: 10 mg/m <sup>3</sup> fume	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume

**Appropriate engineering controls****Engineering controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tight sealing safety goggles.

**Hand protection**

Impervious gloves.

**Skin and body protection**

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.  
Antistatic boots.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations**

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

**9. Physical and chemical properties****Information on basic physical and chemical properties**

<b>Physical state</b>	Aerosol
<b>Appearance</b>	Aerosol
<b>Color</b>	clear; white
<b>Odor</b>	Mild
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flash point	-17 °C / 1.4 °F	None known
Evaporation rate	No data available	< 1 (diethyl ether = 1)
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Relative vapor density	> 1	None known
Relative density	< 1	None known
Water solubility	No data available	Insoluble in water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
<u>Other information</u>		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
Liquid Density	No information available	
Bulk density	No information available	

## 10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

### Acute toxicity

### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5,195.00 mg/kg
ATEmix (dermal)	5,062.40 mg/kg
ATEmix (inhalation-gas)	204,317.80 ppm
ATEmix (inhalation-dust/mist)	99,999.000 mg/l
ATEmix (inhalation-vapor)	99,999.00 mg/l

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rabbit )	-
propane 74-98-6	-	-	> 800000 ppm ( Rat ) 15 min
isobutane 75-28-5	-	-	> 800000 ppm ( Rat ) 15 min
Lithium stearate 4485-12-5	= 15 g/kg ( Rat )	-	-
Precipitated calcium carbonate 471-34-1	= 6450 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 3 mg/L ( Rat ) 4 h
zinc oxide 1314-13-2	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rat )	> 5700 mg/m <sup>3</sup> ( Rat ) 4 h

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** No information available.

**Serious eye damage/eye irritation** No information available.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

<b>STOT - repeated exposure</b>	No information available.
<b>Target organ effects</b>	Respiratory system, Eyes, Skin, Central nervous system.
<b>Aspiration hazard</b>	No information available.
<b>Other adverse effects</b>	No information available.
<b>Interactive effects</b>	No information available.

## 12. Ecological information

### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Distillates (petroleum), hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
zinc oxide 1314-13-2	-	LC50: =1.55mg/L (96h, Danio rerio)	-	-

**Persistence and degradability** No information available.

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
propane 74-98-6	1.09
isobutane 75-28-5	2.8

**Other adverse effects** No information available.

## 13. Disposal considerations

### Disposal methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**California Hazardous Waste Status** This product contains one or more substances that are listed with the State of California as



a hazardous waste.

## 14. Transport information

<b>Note:</b>	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
<b>Special precautions:</b>	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
<b>DOT</b>	Not regulated
<b>Notes</b>	<b>As supplied, this product is consigned under the Limited Quantities provisions.</b>
<b>UN number or ID number</b>	UN1950
<b>Proper shipping name</b>	Aerosols
<b>Transport hazard class(es)</b>	2.1
<b>Hazard label(s)</b>	2.1
<b>Packing group</b>	None
<b>IATA</b>	Not regulated
<b>UN number or ID number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	2.1
<b>Packing group</b>	None
<b>IMDG</b>	Not regulated
<b>UN number or ID number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS
<b>Transport hazard class(es)</b>	2.1
<b>Packing group</b>	None
<b>EmS-No.</b>	F-D, S-U
<b>Marine pollutant</b>	No

Transport Label



DOT Transport Label



## 15. Regulatory information

### International Inventories

<b>TSCA</b>	Complies.
<b>DSL/NDSL</b>	Complies.
<b>EINECS/ELINCS</b>	Complies.
<b>ENCS</b>	Complies.
<b>IECSC</b>	Complies.
<b>KECI</b>	Complies.
<b>PICCS</b>	Complies.

**AIIC** Complies.  
**NZIoC** Complies.

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AIIC** - Australian Inventory of Industrial Chemicals  
**NZIoC** - New Zealand Inventory of Chemicals

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
zinc oxide - 1314-13-2	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
zinc oxide 1314-13-2	-	X	-	-

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	X	X	X
propane 74-98-6	X	X	X
isobutane 75-28-5	X	X	X
Precipitated calcium carbonate	X	X	X

471-34-1			
zinc oxide 1314-13-2	X	X	X
diphenylamine 122-39-4	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. Other information**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Special hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 4	<b>Physical hazards</b> 0	<b>Personal protection</b> X

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

**Key literature references and sources for data used to compile the SDS**

Agency for Toxic Substances and Disease Registry (ATSDR)  
 U.S. Environmental Protection Agency ChemView Database  
 European Food Safety Authority (EFSA)  
 Environmental Protection Agency  
 Acute Exposure Guideline Level(s) (AEGl(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)  
 National Institute of Technology and Evaluation (NITE)  
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
 NIOSH (National Institute for Occupational Safety and Health)  
 National Library of Medicine's ChemID Plus (NLM CIP)  
 National Library of Medicine's PubMed database (NLM PUBMED)  
 U.S. National Toxicology Program (NTP)  
 New Zealand's Chemical Classification and Information Database (CCID)  
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications  
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program  
 Organization for Economic Co-operation and Development Screening Information Data Set  
 World Health Organization

**Revision date** 03/20/2024  
**Revision Note** No information available.

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**