

SAFETY DATA SHEET



Revision date 03/25/2024

Revision Number 4

1. Identification

Product identifier

Product Name Gear Shield Extra Heavy - Aerosol

Other means of identification

Safety data sheet number 05200

Product Code(s) L0152-063

UN number or ID number Not regulated

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

Lubriplate Lubricants Company Headquarters
129 Lockwood St.
Newark, NJ 07105
Midwest Office & Plant
1500 Oakdale Ave.
Toledo, OH 43605
419-691-2491
419-693-3806

Emergency telephone number

Emergency Telephone Chem-Tel 1-800-255 3924 (US & Canada only)
01-813-248-0585 (Outside US & Canada)

2. Hazard(s) identification

Classification

Aspiration hazard	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Hazards not otherwise classified (HNOC)

Not applicable

Label elements**Danger****Hazard statements**

May be fatal if swallowed and enters airways
 Extremely flammable aerosol
 Contains gas under pressure; may explode if heated

**Appearance** Aerosol**Physical state** Aerosol**Odor** Solvent**Precautionary Statements - Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Do not spray on an open flame or other ignition source
 Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF SWALLOWED: Immediately call a POISON CENTER or doctor
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
 Protect from sunlight. Store in a well-ventilated place
 Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

May be harmful in contact with skin. Harmful to aquatic life.

3. Composition/information on ingredients**Substance**

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Trade secret
Distillates (petroleum), hydrotreated light	64742-47-8	30 - <60 %	*
Asphalt, oxidized	64742-93-4	5 - <10%	*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5 - <10%	*
zinc oxide	1314-13-2	1 - <5%	*
Residues (petroleum), atm. tower	64741-45-3	1 - <5%	*
Carbon black	1333-86-4	0.5 - <1.5%	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness.
-----------------	--

Indication of any immediate medical attention and special treatment needed

Note to physicians	Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.
---------------------------	---

5. Fire-fighting measures

Suitable Extinguishing Media Large Fire	Dry chemical. Carbon dioxide (CO ₂). Water spray. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
Explosion data	
Sensitivity to mechanical impact	Yes.
Sensitivity to static discharge	Yes.
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.
---------------------------	---

8. Exposure controls/personal protection

Control parameters

Exposure Limits	The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.
------------------------	--

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	TWA: 5 mg/m ³ inhalable particulate matter excluding metal working fluids, highly & severely refined	TWA: 5 mg/m ³ (vacated) TWA: 5 mg/m ³	IDLH: 2500 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³
zinc oxide 1314-13-2	STEL: 10 mg/m ³ respirable particulate matter TWA: 2 mg/m ³ respirable particulate matter	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ fume (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) STEL: 10 mg/m ³ fume	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
 Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Aerosol
Appearance Aerosol
Color black; Grey
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known

Flash point	-18 °C / -0.4 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	115 psig @ 54°C	None known
Relative vapor density	> 1	None known
Relative density	0.98	None known
Water solubility	No data available	Insoluble in water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	31 cSt @ 100°C/212°F	None known
Dynamic viscosity	No data available	None known

Other information

Explosive properties	Not considered to be explosive
Oxidizing properties	Does not meet the criteria for classification as oxidising
Softening point	No information available
Molecular weight	No information available
VOC content	No information available
Liquid Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information**Information on likely routes of exposure**

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	May be harmful in contact with skin. Repeated exposure may cause skin dryness or cracking.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Acute toxicity**Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	5,149.30 mg/kg
ATEmix (dermal)	2,880.20 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-dust/mist)	99,999.00 mg/l
ATEmix (inhalation-vapor)	99,999.00 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Distillates (petroleum), hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h
Asphalt, oxidized 64742-93-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-
zinc oxide 1314-13-2	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 5700 mg/m ³ (Rat) 4 h
Residues (petroleum), atm. tower 64741-45-3	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	-	>> 4.6 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Asphalt, oxidized 64742-93-4	-	Group 2A	-	X
Carbon black 1333-86-4	A3	Group 2B	-	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target organ effects	Respiratory system, Eyes, Skin, Lymphatic System.
Aspiration hazard	May be fatal if swallowed and enters airways.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Distillates (petroleum), hydrotreated light 64742-47-8	-	LC50: =45mg/L (96h, Pimephales promelas) LC50: =2.2mg/L (96h, Lepomis macrochirus) LC50: =2.4mg/L (96h, Oncorhynchus mykiss)	-	-
Asphalt, oxidized 64742-93-4	EC50: =56mg/L (72h, Pseudokirchneriella subcapitata)	-	-	-
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
zinc oxide 1314-13-2	-	LC50: =1.55mg/L (96h, Danio rerio)	-	-
Residues (petroleum), atm. tower 64741-45-3	-	LC50: =48mg/L (96h, Brachydanio rerio)	-	-

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.


Other adverse effects No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
California Hazardous Waste Status	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

Note:	For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.
Special precautions:	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
DOT	Not regulated
Notes	This product is not regulated for road transportation in accordance with 49 CFR Exceptions.
UN number or ID number	Not regulated
Proper shipping name	Not regulated
Transport hazard class(es)	Not regulated
IATA	
UN number or ID number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Packing group	None
IMDG	
UN number or ID number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	2.1
Packing group	None
EmS-No.	F-D, S-U
Marine pollutant	No
Transport Label	

15. Regulatory information

International Inventories

TSCA	Complies.
DSL/NDL	Complies.
EINECS/ELINCS	Complies.
ENCS	Complies.

IECSC	Complies.
KECI	Complies.
PICCS	Complies.
AIIC	Complies.
NZIoC	Complies.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
zinc oxide - 1314-13-2	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
zinc oxide 1314-13-2	-	X	-	-

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Asphalt, oxidized 64742-93-4	X	-	-
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5	X	X	X

zinc oxide 1314-13-2	X	X	X
Carbon black 1333-86-4	X	X	X
Lithium hydroxide monohydrate 1310-66-3	X	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 2	Flammability 4	Instability 0	Special hazards -
HMIS	Health hazards 2	Flammability 4	Physical hazards 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: Exposure controls/personal protection**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	Sk*	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
U.S. Environmental Protection Agency ChemView Database
European Food Safety Authority (EFSA)
Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGl(s))
U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
U.S. Environmental Protection Agency High Production Volume Chemicals
Food Research Journal
Hazardous Substance Database
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
NIOSH (National Institute for Occupational Safety and Health)
National Library of Medicine's ChemID Plus (NLM CIP)
National Library of Medicine's PubMed database (NLM PUBMED)
U.S. National Toxicology Program (NTP)
New Zealand's Chemical Classification and Information Database (CCID)
Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
Organization for Economic Co-operation and Development High Production Volume Chemicals Program
Organization for Economic Co-operation and Development Screening Information Data Set
World Health Organization

Revision date 03/25/2024
Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet